

DISPLAY TEMPO



Version con cavo:



DISPLAY 4 CIFRE 14CM

Candela: 6.5
Numero di linee: 1
Applicazioni: outdoor e indoor
Dimensioni di ingombro: AxL = 40 x 70 cm
Frontale: antiriflesso
Numero di cifre/linee: 4 (88:88)

Cassone esterno: aluminium, powder coated RAL 7021
Fixed texts: not included
Digit height: 14 cm
LEDs: ultra luminosi rossi
interface: RS232

DISPLAY 6 CIFRE 20CM

Candela: 6.5
Numero di linee: 1
Applicazioni: outdoor e indoor
Dimensioni di ingombro:
A x L = 55 x 90 cm
Frontale: antiriflesso
Numero di cifre/linee: 4 (88:88)

Cassone esterno: aluminium, powder coated RAL 7021
Fixed texts: not included
Digit height: 20 cm
LEDs: ultra bright red
Interface: RS232

Versione wireless:



DISPLAY 4 CIFRE 14CM

Candela: 6.5
Numero di linee: 1
Applicazioni: outdoor e indoor
Dimensioni di ingombro:
A x L = 30 x 70 cm
Frontale: antiriflesso
Numero di cifre/linee:
4 + 1 x colon (88:88)
Possibilities via control panel:
Adjustable race time,
count up/countdown,

HH:MM when race time > 1 hour, MM:SS
when race time < 1 hour
Number of rounds, +1/-1/reset to 0
Cassone esterno: aluminium Q-lite profile,
RAL 7021
LEDs: ultra luminosi rossi
Digit height: 14 cm
Interface: RS232 via Bluetooth
(wireless communication short distance) and
via control panel with LCD-screen with 10m
cable (230VAC)

DISPLAY 6 DIGITS 14 CM

Candela: 6.5
Numero di linee: 1
Applicazioni: outdoor e indoor
Dimensioni A x L = 30 x 100 cm
Frontale: antiriflesso

Numero di cifre/linee: 6 + 2 x colon
(88:88:88)

Cover: aluminium Q-lite profile, RAL 7021
LEDs: Ultra Bright Red
Character height: 14 cm

Power supply: via built-in batteries
(autonomy approximately 10 hours)
Battery charger: is provided

Additional: the backside of the display is
equipped with wire bushes by which a
tube (60 x 60 x 4 mm) can be vertically
assembled by 2 star knobs

Interface: RS232 via Bluetooth (wireless
communication short distance) and via
control panel with LCD-screen with 10m
cable (230VAC)